

FC-200

Windows® Field Controller



Topcon's powerful, rugged, handheld field controller

- BUILT-IN BLUETOOTH® WIRELESS TECHNOLOGY
- ULTRA-BRIGHT, TFT, COLOR TOUCH SCREEN DISPLAY
- WINDOWS® CE.NET 5.0 OPERATING SYSTEM
- INTERNAL WiFi OPTIONAL
- EASY ACCESS COMPACT FLASH AND SD MEDIA CARD SLOTS DELIVER MEMORY EXPANSION AND CONNECTIVITY OPTIONS
- 520MHz XSCALE PROCESSOR
- REMOVABLE, ROBOTIC RADIO
- 128/256MB SDRAM, 256/512MB FLASH ROM

Field Data Comes Alive

If you are looking for a rugged, compact field controller that provides big-time results, look no further than Topcon's FC-200. The FC-200 provides advanced software functions such as the large key pop-up keyboard for data entry and incorporates the graphical Windows® CE.NET 5.0

operating system on a crisp, bright, color touch screen display. Watch your field data come alive with Topcon's FC-200.



Expandability Made Easy

Topcon knows that expandability is important to professionals in the field. The FC-200 allows quick and easy access to SD and CF card slots for data transfer and exchange with other devices. No tools or extra process is needed to access these card slots. In addition, with Bluetooth® wireless technology built-in to the FC-200, the CF card slot remains open for expanded memory.

Removable Robotic Radio

The FC-200 can mount an RS-1 robotic radio on the back of the unit. This compact addition makes the FC-200 the perfect controller for our robotic series of instruments.



Technological Innovators

We know it isn't just about moving dirt or surveying. It's about time, work, energy, manpower, machinery, money, and the countless obstacles that you face everyday. It is our mission here at Topcon to make your job easier, faster, and more affordable—and we have a long history of doing just that. From survey to inspection, Topcon dealers throughout the world supply innovative technology to surveyors, civil engineers, contractors, equipment owners, and contractors, empowering them to improve their productivity, increase their profits, lower their operation costs, and strengthen jobsite safety.

Isn't it time to make building the world of tomorrow a little easier? Welcome to the world of simplicity, accuracy, and precision—welcome to Topcon.



Topcon Positioning Systems, Inc.
7400 National Drive • Livermore, CA 94550
www.topconpositioning.com

Specifications subject to change without notice

©2008 Topcon Corporation All rights reserved. P/N: 7010-0901 Rev. B Printed in U.S.A. 9/08

FC-200 Specifications

Microprocessor	Intel PXA270 XScale
Processor Speed	520MHz
Operating System	Windows® CE.NET 5.0
Memory	128/256MB SDRAM 256/512MB Flash ROM
Interface	Serial RS-232C (D-sub 9) USB USB rev 1.1 (Type Mini-B and Type A) Card Slot SD (SDIO/MMC) Compact Flash (Type I/II)
Bluetooth Capable	Yes
Wireless LAN	Yes (optional)
Display	320 x 240 QVGA (portrait)
Color Sunlight Readable	TFT
Backlight	Backlight (LED)
Keyboard	7 key w/smart keyboard
External Power	Yes
Audio	Sealed Speaker (mono)
Sealed Microphone	Yes
Environmental	IP-66
Operating Temperature	-4°F to +122°F (-20°C to +50°C)
Dimensions	7.72 in. x 4.21 in. x 2.40 in. (196x107x61mm)
Weight	1.6 lbs (720g) (includes batteries)
Batteries	Removable Li-ION rechargeable
Operation	15+ Hrs Single batt (normal use)

Topcon's FC-200 – the powerful, rugged field controller

Design

- Ultra-bright, TFT sunlight-active, color touch screen display
- Wireless connectivity available for Topcon GPS+ and W-series total stations
- Cable-free operation

Durability

- Ruggedized, shock absorbing environmentally sealed housing
- Separately sealed battery makes swapping a snap
- Shock Resistance, 1 meter drop resistant

The compact controller for big-time results

It may be half the size of a conventional controller, but it's every bit as serious about helping you control and collect your critical survey, design and layout jobs, and a lot more fun to use.



Your local Authorized Topcon dealer is:

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Topcon is under license. Other trademarks and trade names are those of their respective owners.